



## PROPELLER CHOICE FOR AM STIRRER

### USAGES

- A . To turbine light bodies
- B . For flocculation
- C . Mixing of thickening agents
- D . Mud agitation
- E . Agitation with good heatexchange of the product
- F . Use for dissolution and disintegration of the particles
- G . To turbine light bodies, flocculation, colouring mixtures
- H . For polymerisation reactions, homogeneous distribution of minerals in fluid substances, suggested for fluid with medium high viscosity

CODE	FIG.	MAX SPEED RPM	20°C VISCOSITY RANGE	USAGES
GT0638	1	< 800	1.000 ÷ 100.000	A B C D
GT0639	2	250 ÷ 800	0 ÷ 10.000	A B C D
GT0640	3	250 ÷ 800	0 ÷ 1.000	A B C D
GT0641	4	250 ÷ 800	1.000 ÷ 10.000	A B C D
GT0642	5	< 250	100 ÷ 10.000	E
GT0643	6	250 ÷ 800	0 ÷ 1.000	A B C D
GT0644	7	< 250	1.000 ÷ 100.000	H
GT0645	8	250 ÷ 800	0 ÷ 10.000	A B C D
GT0646	9	250 ÷ 800	0 ÷ 10.000	A B C D
GT0647	10	250 ÷ 800	1.000 ÷ 100.000	A B F G
GT0648	11	250 ÷ 800	1.000 ÷ 100.000	A B F G