





fig.1



fig.2



TOUCH SCREEN for FLEXI

DESCRIPTION

Touch screen is an accessory supplied with a vesa standard support that can be mounted in easy way because on the flexi column there are 4 holes and a connector for power and electronicl joint ready for it. Touch screen is always programmed and tested. In our plant before delivery. For any problem that could arisen to touch screen the flexi can work in standard mode using the microprocessor installed.

TECHNICAL SPECIFICATIONS

- 7" wide TFT LCD (16:9)
- High Brightness: 450cd/m2
- 800 x 480 resolutions
- 4-wire resistive touch panel
- Power input: DC 9-24VPower consumption: 8W
- Size(LWD): 198×146 ×35mm
- Weight: 740g
- Protection IP64

TOUCH SCREEN

This important accessory allows a better and immediate execution of the tests of strenght on tiles, in addition to making quick and easy to set up and calibrate the instrument

The (fig.2) show in the same screen the load curve and the test report

The dedicated layout is made for speeding setting procedure together an intuitive tests feedback

From the main page fig.1 can easy enter in the configuration page for setting and calibration

Any test can be made in automatic of manual mode

Any report can be printed or sent to the pc and/or be stored in a usb or on pc through software

It is possible to set up to 50 different tiles for testing