



ELECTRONIC ANALYTICAL BALANCES

DESCRIPTION

High precision electronic analytical balances, single range, milligram resolution

TECHNICAL SPECIFICATIONS

- Digital display with integrated key
- Measuring units selection: g, ct, oz, lb, dwt, GN, tL, momme
- Filter for vibrations damping selection
- Automatic calibration by means of reference weight or autocalibration (see model below)
- Tare from 0 (zero) g up to full capacity
- Serial output RS232-C
- Operating temperature: 10 + 30 °C
- Supply: 230 V-50/60 Hz single phase

ACCESSORIES AND SPARE PARTS

GT0412	External printer RS232-C
GT0704	Protection show-case with 3 sliding glasses
GT0705	Connection cable RS232-C balance - PC

CODE	MODEL	CAPACITY	PAN SIZE	RESOLUT.
GT0695	120A	120 g	Ø 80 mm	0,0001 g
GT0697	220 A	220 g	Ø 80 mm	0,0001 g
GT0698	U-120 A	120 g	Ø 80 mm	0,0001 g
GT0700	U-220 A	220 g	Ø 80 mm	0,0001 g
LINEARITY	REPRODUCIB.	CALIBRATION WEIGHT	DIEMENSIONS	WEIGHT
± 0,003 g	0,001 g	External 100 g	194x325x315 mm	8,5 kg
± 0,003 g	0,001 g	External 200 g	194x325x315 mm	8,5 kg
± 0,003 g	0,001 g	Internal Automatic	194x325x315 mm	9 kg