



ELECTRONIC INDUSTRIAL BALANCES

DESCRIPTION

Precision electronic industrial balances single and double range with decigram, gram and decigram/gram resolutions

TECHNICAL SPECIFICATIONS

- Digital display with integrated key
- Measuring units selection: g, ct, oz, lb, dwt, GN, tL, momme
- Filter for vibrations damping selection
- Automatic calibration by means of reference weight
- Tare from 0 (zero) g up to full capacity
- Serial output RS232-C
- Operating temperature: 10 ÷ 30 °C
- Supply: 230V-50/60 Hz single phase

ACCESSORIES AND SPARE PARTS

GT0412	External printer RS232-C
GT0705	Connection cable RS232-C balance - PC

CODE	MODEL	CAPACITY	PAN SIZE	READABILITY
GT0745	16 K	16000 g	320x220 mm	0,1 g
GT2655	25 K	25000 g	320x220 mm	0,1 g
GT2656	32 K	32000 g	320x220 mm	0,1g
GT0749	32 K	32000 g	320x220 mm	1 g

LINEARITY	CALIBRAT. WEIGHT	DIEMENS.	WEIGHT
± 0,3 g	External 5 kg	400x215x165 mm	4,5 kg
± 0,3 g	External 10 kg	400x215x165 mm	4,5 kg
± 0,3 g	External 10 kg	400x215x165 mm	4,5 kg
± 1 g	External 10 kg	400x215x165 mm	4,5 kg