



## ELECTRONIC INDUSTRIAL BALANCES

### DESCRIPTION

Precision electronic industrial balances single and double range with decigram, gram and decigram/gram resolutions.

### TECHNICAL SPECIFICATIONS

- Digital display with integrated key
- Measuring units selection: g, ct, oz, lb, dwt, GN, tl, momme
- Filter for vibrations damping selection
- Automatic calibration by means of reference weight
- Tare from 0 (zero) g up to full capacity
- Serial output RS232-C
- Operating temperature: 10 + 30 °C
- Supply: 230V-50/60 Hz single phase

### ACCESSORIES AND SPARE PARTS

<b>GT0412</b>	External printer RS232-C
<b>GT0705</b>	Connection cable RS232-C balance - PC
<b>GT0706</b>	Connection cable RS232-C balance - printer

CODE	MODEL	CAPACITY	PAN SIZE	READABILITY.	LINEARITY	CALIBRAT. WEIGHT	DIEMENS.	WEIGHT
<b>GT0745</b>	16 K	16000 g	320x220 mm	0,1 g	± 0,3 g	External 5 kg	400x215x165 mm	4,5 kg
<b>GT2655</b>	25 K	25000 g	320x220 mm	0,1 g	± 0,3 g	External 10 kg	400x215x165 mm	4,5 kg
<b>GT2656</b>	32 K	32000 g	320x220 mm	0,1g	± 0,3 g	External 10 kg	400x215x165 mm	4,5 kg
<b>GT0749</b>	32 K	32000 g	320x220 mm	1 g	± 1 g	External 10 kg	400x215x165 mm	4,5 kg
<b>GT0752</b>	4530	4500/32000 g	320x220 mm	0,1/1 g	± 0,01/1 g	External 2 kg	400x215x165 mm	4,5 kg