




CODE **GT1915**
MODEL **ISOVACUUM 650**
OVERALL DIMENSIONS 1280x580x1140 mm
POWER 0,5 kW
WEIGHT 130 Kg

CODE **GT1917**
MODEL **ISOVACUUM 650x1250**
OVERALL DIMENSIONS 1900x580x1140mm
POWER 0,5 kW
WEIGHT 280 Kg

CODE **GT1916**
MODEL **ISOVACUUM 800**
OVERALL DIMENSIONS 1330x580x1150 mm
POWER 0,5 kW
WEIGHT 150 Kg

CODE **GT1918**
MODEL **ISOVACUUM 950**
OVERALL DIMENSIONS 1580x580x1300 mm
POWER 0,5 kW
WEIGHT 240 kg



TOUCH SCREEN

ISOVACUUM

STANDARDS

UNI EN ISO 10545-3:2018, UNI EN ISO 10545-12, ASTM C373-16

DESCRIPTION

The instrument performs the a.b. tests and in addition also for the latest forthcoming standard 10545-3 (2018) for cut tiles 20x20 cms. All the cycles are pre-programmed and the operator can easily select them or modify the existing ones or programming new ones. The colour touch screen presents an easy interface that allows to enter a lot of informations.

The instruments are tested and calibrated according to the UNI EN ISO 10545-3:2018 others standard on demand.

TECHNICAL SPECIFICATIONS

- Touch screen with working cycle display.
- Friendly and easy use of the instrument by means of the touch-screen that allows controlling the working cycle parameters and display of the cycle trend.
- Display of the working cycle trend.
- Saving time of working cycle duration.
- Absolute pressure sensor.
- Vertical tank with different levels steel basket.
- Pump for water discharge.
- Reaching and keeping the pressure ± 1 Kpa.
- Water filling level.
- Control of the warning water level.
- Nr.10 programmable working cycles.
- Data logger of the cycle.
- Exporting data by USB (pen drive).
- Ethernet output predisposition.
- Possibility of calibrating the instrument by means of calibrated gauge.
- Alarms setting.
- Predicted maintenance:
 - Pump oil level control
- Power supply: 230V-50 Hz single phase (other voltages on request)

EQUIPMENT

- Holder tiles basket all made stainless steel AISI-304
- Bottle of special oil for pump 500 cc

ACCESSORIES AND SPARE PARTS

GT2123	Microfiber Cloth 40x40 cm
GT1683	Vacuum pump
GT1684	Bottle 500 cc special oil for pump
GT0971	Plastic tank for demineralized water 500 Lt. (Model 800, 950, and 1250)
GT1471	Plastic tank for demineralized water 300 Lt (Model 650)
GT2088	Accredia reference vacuumeter
GT2343	Reference vacuumeter