



CODE **GT1608**
 MODEL **ISOVACUUM 650**
 USEFUL DIMENSIONS 650x250x650 mm
 OVERALL DIMENSIONS 950x500x1000 mm
 POWER 0,50 kW
 WEIGHT 130 Kg



CODE **GT1484**
 MODEL **ISOVACUUM 650x1250**
 USEFUL DIMENSIONS 650x250x1250 mm
 OVERALL DIMENSIONS 1500x580x950 mm
 POWER 0,80 kW
 WEIGHT 280 Kg



CODE **GT1356**
 MODEL **ISOVACUUM 800**
 USEFUL DIMENSIONS 800x250x800 mm
 OVERALL DIMENSIONS 1180x580x1150 mm
 POWER 0,5 kW
 WEIGHT 150 Kg

CODE **GT1685**
 MODEL **ISOVACUUM 950**
 USEFUL DIMENSIONS 950x250x950 mm
 POWER 0,8 kW
 WEIGHT 240 kg

ISOVACUUM

STANDARDS

UNI EN ISO 10545-3, UNI EN ISO 10545-12, ASTM C-1026-87, GOST 27180

DESCRIPTION

Laboratory instrument to establishing the water absorption under vacuum of ceramic tiles with automatic cycles. Vacuum test takes place as follows: lay the tiles onto a suitable grid into the tank; switch on the vacuum pump. By doing so it shall be possible to determine the apparent porosity, the apparent relative density and the absorption of water.

*The instruments was tested to do ISO and ASTM STANDARD.
 WORKS DEPRESSIONS (0 ÷980 - mbar).*

TECHNICAL SPECIFICATIONS

- Vacuum pump for tests UNI EN ISO, ASTM and GOST.
- Selection for 2 water level by means of electronic sensor.
- Working cycles: ISO, ASTM and GOST.
- Supply: 230 V - 50 Hz single phase (other voltage on request).
- Time variation of the phase (other voltage on request).

EQUIPMENT

- Holder tiles basket all made stainless steel AISI-304.
- Bottle of special oil for pump 500 cc.

ACCESSORIES AND SPARE PARTS

GT2123	Chamois leather
GT0138	Vacuum pump
GT1324	Bottle 500 cc special oil for pump
GT0971	Plastic tank for demineralized water 500 Lt. (Model 800 and 950)
GT1471	Plastic tank for demineralized water 300 Lt (Model 650)