



CODE **GT2652**
MODEL **PRESS 25 TON PLUS**
EXTERNAL DIMENSIONS 900x600x1300 mm
MAXIMUM FORCE APPLIED 25 Ton
WEIGHT 330 Kg
POWER 750 W
VOLTAGE 230V 1ph 50Hz

PRESS 25 TON PLUS

STANDARDS

EN 196-1 | EN 1015-11 | ISO 679 ASTM C109 | ASTM C349 | ASTM D1194 | DIN 1164 |
BS 4550 | GOST 26798.1 | API RP 19 | CEN ISO 13503-2

DESCRIPTION

Press 250 kN / 25 Ton with control unit for semi-automatic control suitable for carrying out compression tests on portions of prism 40.1x40x160 mm, cubic side 40, 50, 70, 100 mm and 2"; samples with max. of 180 mm.

TECHNICAL SPECIFICATIONS

- High rigidity two-column frame
- Maximum vertical daylight between floors: 185 mm.
- Plate diameter: 153 mm.
- Piston stroke: 45 mm.
- Accuracy: Grade 1 starting from 1/10 of the scale.
- Supplied complete with lower compression plate and fitting for easy attachment of the compression device.
- Power supply: 230V 1ph 50Hz 750W.
- Weight: 300 – 330 kg.